

Tooling for Boschert Copper punching machines



Station B 1-1/4" ps:®beta-V2-CU-15	Station B 1-1/4" ps:®beta-V2-CU-20	Station C 2" Standard-CU-15	Station C 2" Standard-CU-20	Station D 3-1/2" Standard-CU-15	Station D 3-1/2" Standard-CU-20	8-Station Multitool MTB8X-16-CU-15	3-Station Multitool MTB3B-31,75-CU-20	Slitting Tool ps:®slitting-CU-15	Slitting Tool ps:®slitting-CU-20	Single Tapping Tool ps:®single-thread-CU	3-Station Tapping Tool ps:®triple-thread-CU
Diameter up to 1.250" (31.75mm) Thickness up to 0.591" (15mm)	Diameter up to 1.250" (31.75mm) Thickness up to 0.787" (20mm)	Diameter up to 2.000" (50.8mm) Thickness up to 0.591" (15mm)	Diameter up to 2.000" (50.8mm) Thickness up to 0.787" (20mm)	Diameter up to 3.500" (88.9mm) Thickness up to 0.591" (15mm)	Diameter up to 3.500" (88.9mm) Thickness up to 0.787" (15mm)	Diameter up to 3-1/2" (16mm) Thickness up to 0.630" (15mm)	Diameter up to 1.250" (31.75mm) Thickness up to 0.787" (20mm)	RE 0.315" x 2.362" (8x60mm) Thickness up to 0.630" (15mm)	RE 0.472" x 1.772" (12x45mm) Thickness up to 0.787" (20mm)	M3 to M16 UNC1/8"-40 to #12-24 Thickness up to 0.787" (20mm)	M3 to M16 UNC1/8"-40 to #12-24 Thickness up to 0.787" (20mm)